



CCFPRO-TH-HV-R

CLEVERTRONICS LP CLEVERFIT PRO EXIT – THEATRE MASK



PRODUCT INFORMATION

Part Number	CCFPRO-TH-HV-R
MIC	AUA02860030001
Description	LP Premium Cleverfit Pro Emergency Exit, Theatre Mask
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Single-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask Running man (Must specify diffuser combination)
Lamp(s)	6 x Duris LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	BATT:LP 3.2V 1100mAh 260mm lead,no BRKT
8003156	PCA:CCF-Pro #CT10622 6C20 DALI REG
8002710	PCA:DurisLED Strip Clvrft Pro CT10276-D3
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order