



CIRC-SEN

Circlite, Non-emergency, Switchable Colour, Motion Sensor,
White



PRODUCT INFORMATION	
Part Number	CIRC-SEN
MIC	AUC04610060001
Description	Circlite, Non-emergency, Switchable Colour, Motion Sensor, White
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Switchable output	N/A
Material	Base & Diffuser: Polycarbonate
Mounting	Ceiling/Wall Surface Mount
Sensor Capability	Microwave, High/Low, Master Slave - No
Dimensions	Ø350mm x 81mm
Weight	1.43kg
Operating Mode	N/A
Testing System	N/A
Battery	N/A
Charging Method	N/A
Driver	30W Stallion, MS-HL2, 500mA output N/A
Lamp(s)	LED Panel, 3,000K warm white, 4,000K natural white, 5,700K cool white, Ra>80 L70/B50 Ta 40°C; LM80 Report >54,000hr, Projected 166,000hr L70/B50 Ta 25°C; LM80 Report >54,000hr, Projected 166,000hr L80/B20 Ta 40°C; LM80 Report >54,000hr, Projected 94,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	220-240V~ 50Hz
Total Lumen Output	2257 lm (110.1 lm/W) @default (refer to next page for details)
Power Consumption	21.12W (refer to next page for details)
Supply Current	0.10A +/-20 mA
Inrush Current (Max)	6.90A<34 μs
Earth Leakage	0.127mA
IP Rating	IP20
IK Rating	IK03
LED MacAdam	5
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Applicable Standards	AS/NZS3820, AS/NZS60598, CISPR15
Compliance Marking	



CIRC-SEN

Circlite, Non-emergency, Switchable Colour, Motion Sensor,
White

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
N/A	Battery
1330103	240V Driver
8051425	LED Panel
N/A	Emergency Driver
1190134	Sensor

Power Consumption & Lumen Output	Output (500mA)		
	Lamp On	Lamp On, Min 10%	Lumen Output
3000K	21.1W	2.9W	2141 lm
4000K	20.5W	2.9W	2257 lm
5700K	21.1W	2.9W	2192 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order