



## CIRC-DD-LP-D2

Circlite, Emergency, LP, Switchable Colour, DALI Driver,  
DALI-2 Emergency, White



PRODUCT INFORMATION	
Part Number	CIRC-DD-LP-D2
MIC	AUC02210070001
Description	Circlite, Emergency, LP, Switchable Colour, DALI Driver, DALI-2 Emergency, White
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Material	Base & Diffuser: Polycarbonate
Mounting	Ceiling/Wall Surface Mount
Sensor Capability	N/A
Dimensions	Ø350mm x 81mm
Weight	1.57kg
Operating Mode	Sustained
Testing System	DALI-2
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Driver	Driver LCA 35W 150-700mA one4all lp PRE
Lamp(s)	LED Panel, 3,000K warm white, 4,000K natural white, 5,700K cool white, Ra>80 L70/B50 Ta 40°C; LM80 Report >54,000hr, Projected 166,000hr L80/B20 Ta 40°C; LM80 Report >54,000hr, Projected 94,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	220-240V~ 50Hz
Total Lumen Output	2257 lm (115 lm/W) @default (refer to next page for details)
Power Consumption	19.5W (refer to next page for details)
Supply Current	0.101A +/-20mA
Inrush Current (Max)	13.6A < 304 µs
Earth Leakage	0.455mA
IP Rating	IP20
IK Rating	IK03
LED MacAdam	<5
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, AS/NZ60598-2-22, CISPR15, AS/NZS2293.3
Compliance Marking	



## CIRC-DD-LP-D2

Circlite, Emergency, LP, Switchable Colour, DALI Driver,  
DALI-2 Emergency, White

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	Battery
1330067	240V Driver
8051420	LED Panel
AUM02270780001 CLEDDRV2CH-RR-3C200-3C200-CKIT-D2	Emergency Driver

Power Consumption & Lumen Output	Output (500mA) Power Consumption			Total Lumen Output
	MAX Charge Lamp ON	Standby Lamp ON	Standby Lamp OFF	
3000K	21.1W	20.1W	0.7W	2141 lm
4000K (DEFAULT)	20.5W	19.5W	0.7W	2257 lm
5700K	21.0W	20.1W	0.7W	2192 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order