



CIRC-DD

Circlite, Non-emergency,
Switchable Colour & Output, White



PRODUCT INFORMATION	
Part Number	CIRC-DD
MIC	AUC04610070001
Description	Circlite, Non-emergency, Switchable Colour & Output, White
Colour CCT	Switchable 3000K / 4000K (Default) / 5700K
Switchable output	High (Default) / Low
Material	Base & Diffuser: Polycarbonate
Mounting	Ceiling/Wall Surface Mount
Sensor Capability	N/A
Dimensions	Ø350mm x 81mm
Weight	1.22kg
Operating Mode	N/A
Testing System	N/A
Battery	N/A
Charging Method	N/A
Driver	30W Stallion, SP2, Dip Switch, 250/500mA
Lamp(s)	LED Panel, 3,000K warm white, 4,000K natural white, 5,700K cool white, Ra>80 L70/B50 Ta 40°C; LM80 Report >54,000hr, Projected 166,000hr L70/B50 Ta 25°C; LM80 Report >54,000hr, Projected 166,000hr L80/B20 Ta 40°C; LM80 Report >54,000hr, Projected 94,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr
Operating Voltage	220-240V~ 50Hz
Total Lumen Output	2257 lm (112.8 lm/W) @default (refer to next page for details)
Power Consumption	18.8W (refer to next page for details)
Supply Current	0.09A +/-20mA
Inrush Current (Max)	7.10 A < 28 µs
Earth Leakage	0.125mA
IP Rating	IP20
IK Rating	IK03
LED MacAdam	5
Operating Temperature	1°C to 40°C
AS2293 Classification	NA
Applicable Standards	AS/NZS3820, AS/NZS60598, CISPR15
Compliance Marking	



CIRC-DD

Circlite, Non-emergency,
Switchable Colour & Output, White

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
N/A	Battery
1330102	240V Driver
8051425	LED Panel
1330067	Emergency Driver
N/A	Sensor

Power Consumption & Lumen Output	Output (500mA)	
	Lamp On	Lumen Output
3000K	19.4W	2141 lm
4000K	18.8W	2257 lm
5700K	19.4W	2192 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order