

CLEVERTRONICS L10 LED SUPALITE (ZONWORKS HIVE)



PRODUCT INFORMATION

Catalogue Number	LFLLED-HVG
MIC	UKE01810010001
Description	L10 Optimum Supalite LED Flood Unit, Surface Mounted Emergency Light
Construction	Polycarbonate
Mounting	Surface Mounted.
Dimensions L x W x H	Main enclosure - 282mm (W) x 137mm (H) x 64mm (D) Total height including LED Heads 225mm.
Weight	1.3kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type and Manufacturer	Lithium Nanophosphate, Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED Heads (adjustable), 160lm per lamp head
Operating Voltage	240V AC; 50Hz
Total lumen output	320lm (Emergency total)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) 				
Luminaire Classification	<table border="1"> <tr> <td>X</td> <td>0</td> <td>ADF</td> <td>180</td> </tr> </table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598.2.22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY: L10 3.3V 5AH. 200mm lead, Brkt.
1100955	LED Flood Lamp Head Ass,Cable&Cnnctr, Right
1100954	LED Flood Lamp HeadAss,Cable&Cnnctr,Left
HVG-RF-NODE-INT	UK RF Node CT10720-Ax Int Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.