



# CLIFE-HVG

## CLEVERTRONICS CLP LIFELIGHT (ZONWORKS HIVE)



PRODUCT INFORMATION	
Part Number	CLIFE-HVG
MIC	UKD02810060001
Description	CLP Premium Lifelight, High Performance, Recessed Emergency Light
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack), 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.4 Watts (Standby), 4.7 Watts (Max)
Total lumen output	200lm (Emergency)

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



# CLIFE-HVG

CLEVERTRONICS CLP LIFELIGHT  
(ZONWORKS HIVE)

## PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550092	Battery
1100923	Emergency LED
UKM02870020001 CLIFE-CKIT-HVG-500	Emergency Driver Pack
8003330	Communication Node - Hive

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.