

CLEVERTRONICS CLP LIFELIGHT SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CLIFE-SM
MIC	UKD02310040001
Description	CLP Premium LifeLight, High Performance, Recessed Emergency Light with Clevertest Plus Enabled
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	200lm (Emergency)
Power Consumption	1.0 Watts (Standby), 4.2 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 			
Luminaire Classification	X	0	AD	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8002942	PCA: CLIFE CT10260-L5 1C500 UK CTP Vert Connectors

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.