



LJWELED-50-HVG

CLEVERTRONICS L10 JUMBO WEATHERPROOF UNIVERSAL EXIT



PRODUCT INFORMATION

Part Number	LJWELED-50-HVG				
MIC	UKA01820030001				
Description	L10 Optimum Jumbo Weatherproof Emergency Exit, 50 Metre Viewing Distance, Universal Mounting				
Construction	Polycarbonate				
Mounting	Wall Mount, Single-sided Ceiling Mount, Single & Double-sided				
Dimensions L x W x H	570mm x 117mm x 340mm				
Weight	5.6kg				
Operating Mode	Maintained				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Nanophosphate, Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Diffuser	All Directional Inserts Included in the Box				
Lamp(s)	12 x LED Lamp Bar Assembly 100,000 Hours				
Operating Voltage	220-240V AC; 50Hz				
Total lumen output	92lm (Downward Emergency Output)				
Power Consumption	3.2W (Standby), 5.1W (Max)				
Viewing Distance	50m				
Rated Emergency Duration	180 minutes				
IP Rating	IP66				
IK Rating	IK09				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery Overvoltage & Overcurrent Protection• Battery Deep Discharge Protection• Supply Voltage Polarity Reversal Protection• Battery Short-circuit Protection (Charging Will Resume Upon Removal of Fault)• Kit Box (Enclosure) of Lamp Control Gear Provides Protection Against Accidental Contact with Live Parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8050640	LED Panel
UKM01870130001	Driver Pack
8003330	Node - HIVE