

ULTRABLADE PRO SURFACE MOUNT EXIT LIGHT



Surface Mounted Architectural Blade Exit Light

The Ultrablade Pro Surface Mount Exit is designed to satisfy architectural requirements in applications where a higher level of sophistication is required.

With the latest lithium battery and LED technology, maintenance and energy costs will be significantly reduced when compared to many alternatives.




Applications

-  Office Buildings
-  Retail outlets
-  Galleries
-  Apartments
-  Shopping Centres



Features and Benefits

- Tested to BS EN 60598-2-22
- Compliant to EN1838 and ISO7010
- Low 1.8W standby power consumption
- Wall and ceiling mount
- All directional decals in one box
- Lithium Iron Phosphate or Nanophosphate® battery
- DALI® and Zoneworks® test options available
- Clevertest Plus System compatible



ULTRABLADE PRO SURFACE MOUNT EXIT LIGHT


ORDERING INFORMATION		CLP		L10	
PART NO	Standard	CUBPRO-SM		LUBPRO-SM	
	Clevertest Plus System Compatible	Yes			
	DALI	CUBPRO-SM-DALI		LUBPRO-SM-DALI	
	Zoneworks® XT Hive	CUBPRO-SM-HVG		LUBPRO-SM-HVG	
	Theatre Version	CUBPRO-SM-TH		LUBPRO-SM-TH	
Carton Quantity	5				
Weight - single (carton)	1.1kg (5.5kg)				
Dimensions (L x W x H)	317mm x 8.7mm x 157mm - Blade Assembly 360mm x 47mm x 72mm - Base				
Directional Options	All Directional Inserts Included (Excluding theatre versions)				
Directional Options (Theatre Only)	Add Suffix to Part No, Double Sided -DS, Left Arrow -RL, Right -RR, Up -RU, Down -RD. eg CUBPRO-SM-TH-DS-RL				

POWER, LAMPS AND BATTERY		CLP		L10	
Power Consumption (Standby / Max)	1.8W / 3.9W		1.9W / 4.1W		
Lamp(s)	100,000 Hour LED				
Battery	Lithium Iron Phosphate		Lithium Nanophosphate®		
Voltage (V) / Capacity (mAh)	3.2V / 1500mAh		3.3V / 2500mAh		
Charging Method	Intelligent Current Limited Constant Voltage				
Rated Emergency Duration (Mins)	180				

TECHNICAL SPECIFICATIONS		CLP		L10	
Operating Mode	Maintained				
Voltage (V) Frequency (Hz)	220-240V (50Hz)				
Construction - Body / Diffuser	PC-ABS / PC				
Viewing Distance	30m				
Mounting Type	Wall & Ceiling Mount (Single & Double Sided)				
Operating Temperature	0°C to 40°C				
IP Rating (IP)	IP20				

LUMINAIRE CLASSIFICATION		CLP				L10			
Without Automatic Testing	X	1	AG	180	X	1	AG	180	
With Automatic Testing	X	1	AFG	180	X	1	AFG	180	

PROTECTION	
Battery overvoltage & overcurrent protection	
Battery deep discharge protection	
Supply voltage polarity reversal protection	
Battery short-circuit protection (charging will resume upon removal of fault)	



Dimensions (mm)

*Warranty information located at: <https://clevertronics.co.uk/product-warranty-statement/>

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

clevertronics.co.uk

362 Stockley Close, West Drayton, London UB7 9BL

Clevertronics International UK Ltd trading as Clevertronics, with registered number 11249539, whose registered office is at 843 Finchley Road London NW11 8NA. 248UK UK Catalogue 2021

