

FORM EXIT LIGHT



Architectural Exit for all Applications

The Form 20m Exit strikes a balance between Form & Function. Featuring an elegant and size optimised anodised aluminium frame, the Form is a versatile architectural solution available in multiple configurations including wall, ceiling, recessed, or suspended rod or cable mounting. Designed for simplified installation and maintenance, it also features our industry leading 'One-Box' solution that allows easy changing of directional decals as required.

Applications

-  Office Buildings
-  Retail outlets
-  Galleries
-  Apartments
-  Shopping Centres



Features and Benefits

- Tested to BS EN 60598-2-22
- Compliant to EN1838 and ISO7010
- 'One Box' solution with all changeable directional decals included
- Optional escape route illumination
- Surface or recessed mount
- Low standby power consumption
- Up to IP42 Ingress Protection (Surface Wall Mount)
- Lithium Iron Phosphate or Nanophosphate® battery
- DALI and Zoneworks test options available
- Clevertest Plus System compatible



FORM EXIT LIGHT – WALL MOUNT

| ORDERING INFORMATION | | CLP | | L10 | | CLP | | L10 | |
|-----------------------------------|--|--|--|------------------------|--|---|--|-------------------------|--|
| Mounting Configuration | | Wall Mount - Surface | | | | Wall Mount - Recessed | | | |
| Standard | | FORM-20-SM-WM-LP | | FORM-20-SM-WM-L10 | | FORM-20-REC-WM-LP | | FORM-20-REC-WM-L10 | |
| Clevertest Plus System Compatible | | Yes | | | | Yes | | | |
| DALI | | FORM-20-SM-WM-LP-DALI | | FORM-20-SM-WM-L10-DALI | | FORM-20-REC-WM-LP-DALI | | FORM-20-REC-WM-L10-DALI | |
| Zoneworks® XT Hive | | FORM-20-SM-WM-LP-HVG | | FORM-20-SM-WM-L10-HVG | | FORM-20-REC-WM-LP-HVG | | FORM-20-REC-WM-L10-HVG | |
| Escape Route Illumination | | *Yes (Add '-ESC' to end of product codes above) | | | | | | | |
| Carton Quantity | | 1 | | | | | | | |
| Weight - Single (Standard) | | 0.55kg | | | | 0.7kg | | | |
| Dimensions (L x W x H) | | 220mm x 18mm x 110mm - Blade Assembly 211mm x 26mm x 101mm - Body / Box | | | | 220mm x 18mm x 110mm - Blade Assembly 200mm x 52mm x 90mm - Body / Box | | | |
| Directional Options | | All Directional Inserts Included | | | | | | | |

| POWER, LAMPS AND BATTERY | | CLP | | L10 | | CLP | | L10 | |
|------------------------------------|--|--|--|------------------------|--|------------------------|--|------------------------|--|
| Power Consumption (Standby / Max)* | | 1.2W / 3.3W | | | | | | | |
| Lamp(s)* | | 170,000 Hour LEDs | | | | | | | |
| Battery Type | | Lithium Iron Phosphate | | Lithium Nanophosphate® | | Lithium Iron Phosphate | | Lithium Nanophosphate® | |
| Battery Configuration | | Integral | | | | | | | |
| Voltage (V) / Capacity (mAh) | | 3.2V / 1100mAh | | 3.3V / 2500mAh | | 3.2V / 1100mAh | | 3.3V / 2500mAh | |
| Charging Method | | Intelligent Current Limited Constant Voltage | | | | | | | |

* Please refer to the specific product datasheet for actual power consumption and lamp life


| TECHNICAL SPECIFICATIONS | | CLP | | L10 | | CLP | | L10 | |
|--------------------------------|--|--|--|-----|--|-----------------|--|-----|--|
| Operating Mode | | Maintained | | | | | | | |
| Voltage (V) Frequency (Hz) | | 220-240V (50Hz) | | | | | | | |
| Construction - Blade Assembly | | Anodised Aluminium Frame & Polycarbonate Housing | | | | | | | |
| Construction - Body / Box | | Polycarbonate | | | | PCM Sheet Metal | | | |
| Viewing Distance | | 20m | | | | | | | |
| Operating Temperature | | 0°C to 40°C | | | | | | | |
| Ingress Protection Rating (IP) | | IP42 | | | | IP20 | | | |
| Impact Rating (IK) | | IK03 | | | | | | | |

| LUMINAIRE CLASSIFICATION | | CLP | | L10 | | CLP | | L10 | |
|---------------------------|--|-----|---|-----|-----|-----|---|-----|-----|
| Without Automatic Testing | | X | 1 | AG | 180 | X | 1 | AG | 180 |
| With Automatic Testing | | X | 1 | AFG | 180 | X | 1 | AFG | 180 |

| PROTECTION |
|---|
| Battery overvoltage & overcurrent protection |
| Battery deep discharge protection |
| Supply voltage polarity reversal protection |
| Battery short-circuit protection (charging will resume upon removal of fault) |


SURFACE MOUNT

WALL MOUNT - SURFACE



RECESSED

WALL MOUNT - RECESSED



FORM EXIT LIGHT – CEILING MOUNT

| ORDERING INFORMATION | | CLP | | L10 | | CLP | | L10 | |
|-----------------------------------|--|---|--|--------------------------|--|---|--|---------------------------|--|
| Mounting Configuration | | Ceiling Mount - Surface (Single & Double Sided) | | | | Ceiling Mount - Recessed (Single & Double Sided) | | | |
| Standard | | FORM-20-SM-CM-LP | | FORM-20-SM-CM-L10 | | FORM-20-REC-CM-LP | | FORM-20-REC-CM-L10 | |
| Clevertest Plus System Compatible | | Yes | | | | | | | |
| DALI | | FORM-20-SM-CM-LP-DALI | | FORM-20-SM-CM-L10-DALI | | FORM-20-REC-CM-LP-DALI | | FORM-20-REC-CM-L10-DALI | |
| Zoneworks® XT Hive | | FORM-20-SM-CM-LP-HVG | | FORM-20-SM-CM-L10-HVG | | FORM-20-REC-CM-LP-HVG | | FORM-20-REC-CM-L10-HVG | |
| Escape Route Illumination | | Yes (Add '-ESC' to end of product codes above) | | | | | | | |
| Rod Suspended* | | FORM-20-SM-CM-RS-LP | | FORM-20-SM-CM-RS-L10 | | FORM-20-REC-CM-RS-LP | | FORM-20-REC-CM-RS-L10 | |
| Cable Suspended* | | FORM-20-SM-CM-CS-LP | | FORM-20-SM-CM-CS-L10 | | FORM-20-REC-CM-CS-LP | | FORM-20-REC-CM-CS-L10 | |
| Cable Suspended - Remote Gear* | | FORM-20-SM-CM-CS-REM-LP | | FORM-20-SM-CM-CS-REM-L10 | | FORM-20-REC-CM-CS-REM-LP | | FORM-20-REC-CM-CS-REM-L10 | |
| Flag Mount Bracket Available* | | Yes | | Yes | | - | | - | |
| Carton Quantity | | 1 | | | | | | | |
| Weight - Single (Standard) | | 0.8kg | | | | 0.7kg | | | |
| Dimensions (L X W X H) | | 220mm x 18mm x 110mm - Blade Assembly 220mm x 58mm x 45mm - Body / Box 1500mm x 5mm Ø Rod 1500mm x 1.4mm Ø Cable | | | | 220mm x 18mm x 110mm - Blade Assembly 228mm x 63mm x 55mm - Body / Box 245mm x 85mm - Cover Plate 1500mm x 5mm Ø Rod 1500mm x 1.4mm Ø Cable 230mm x 65mm - Cut Out | | | |
| Directional Options | | All Directional Inserts Included | | | | | | | |

*Escape Route Illumination not available

| POWER, LAMPS AND BATTERY | | CLP | | L10 | | CLP | | L10 | |
|------------------------------------|--|--|--|------------------------|--|------------------------|--|------------------------|--|
| Power Consumption (Standby / Max)* | | 1.2W / 3.3W | | | | | | | |
| Lamp(s)* | | 170,000 Hour LEDs | | | | | | | |
| Battery Type | | Lithium Iron Phosphate | | Lithium Nanophosphate® | | Lithium Iron Phosphate | | Lithium Nanophosphate® | |
| Battery Configuration | | Integral | | | | | | | |
| Voltage (V) / Capacity (mAh) | | 3.2V / 1100mAh | | 3.3V / 2500mAh | | 3.2V / 1100mAh | | 3.3V / 2500mAh | |
| Charging Method | | Intelligent Current Limited Constant Voltage | | | | | | | |

*Please refer to the specific product datasheet for actual power consumption and lamp life

| TECHNICAL SPECIFICATIONS | | CLP | | L10 | | CLP | | L10 | |
|--------------------------------|--|--|--|-----|--|-----------------|--|-----|--|
| Operating Mode | | Maintained | | | | | | | |
| Voltage (V) Frequency (Hz) | | 220-240V (50Hz) | | | | | | | |
| Construction - Blade Assembly | | Anodised Aluminium Frame & Polycarbonate Housing | | | | | | | |
| Construction - Body / Box | | Powder Coated Cast Aluminum | | | | PCM Sheet Metal | | | |
| Viewing Distance | | 20m | | | | | | | |
| Operating Temperature | | 0°C to 40°C | | | | | | | |
| Ingress Protection Rating (IP) | | IP20 | | | | | | | |
| Impact Rating (IK) | | IK03 | | | | | | | |


| LUMINAIRE CLASSIFICATION | | CLP | | L10 | | CLP | | L10 | |
|---------------------------|--|-----|---|-----|-----|-----|---|-----|-----|
| Without Automatic Testing | | X | 1 | AG | 180 | X | 1 | AG | 180 |
| With Automatic Testing | | X | 1 | AFG | 180 | X | 1 | AFG | 180 |

| PROTECTION | |
|------------|---|
| | Battery overvoltage & overcurrent protection |
| | Battery deep discharge protection |
| | Supply voltage polarity reversal protection |
| | Battery short-circuit protection (charging will resume upon removal of fault) |


FORM EXIT LIGHT – CEILING MOUNT

SURFACE MOUNT


CEILING MOUNT - SURFACE



CEILING MOUNT - SURFACE
ROD SUSPENDED




CEILING MOUNT - SURFACE
CABLE SUSPENDED




RECESSED


CEILING MOUNT - RECESSED




CEILING MOUNT - RECESSED
ROD SUSPENDED



CEILING MOUNT - RECESSED
CABLE SUSPENDED



CEILING MOUNT - RECESSED
CABLE SUSPENDED - REMOTE GEAR



*Warranty information located at: <https://clevertronics.co.uk/product-warranty-statement/>

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

clevertronics.co.uk

362 Stockley Close, West Drayton, London UB7 9BL
Clevertronics International UK Ltd trading as Clevertronics, with registered number 11249539, whose registered office is at 843 Finchley Road London NW11 8NA. _UK Form Exit 06OCT22

