



LLIFE-PRO-SM-WP-WL

CLEVERTRONICS L10 LIFELIGHT PRO IP65 WEATHERPROOF
SURFACE MOUNT EMERGENCY WITH WAREHOUSE LENS



PRODUCT INFORMATION					
Part Number	LLIFE-PRO-SM-WP-WL				
MIC	UKT01320120001				
Description	L10 Optimum Lifelight PRO, High Performance, Weatherproof, Surface Mounted Emergency Light with Warehouse Lens, Enabled with Clevertest Plus				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	2 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	386lm (Emergency)				
Power Consumption	0.4W (Standby) 2.7W (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530231	Battery
8050880	LED Strip
8002958	Driver Pack

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice