

BULKITE EMERGENCY LUMINAIRE




Durable Bulkhead Luminaire

The Bulklite is a durable and weatherproof IK08 impact rated LED emergency luminaire that can be easily configured to an exit sign using optional directional legends.

Made from UV stabilised polycarbonate and featuring efficient long life LED's and lithium battery power, the Bulklite is designed for robust wall or ceiling applications.

Applications

- | | |
|---|---|
|  Apartments |  Car Parks |
|  Factories |  Public Amenities |
|  Schools |  Sports Facilities |



Features and Benefits

- Tested to BS EN 60598-2-22
- Low 0.4W standby power consumption
- Wall and ceiling mount
- IP65 weatherproof
- IK08 impact protection
- Directional decals available separately
- DALI® and Zoneworks® test options available
- Clevertest Plus System compatible



BULKITE EMERGENCY LUMINAIRE

ORDERING INFORMATION		CLP	L10
TEST OPTIONS / PART NO	Standard	CBULK	LBULK
	Carton Quantity	1	
	Weight - single (carton)	2.0kg	
	Clevertest Plus System compatible	Yes	
	DALI	CBULK-DALI	LBULK-DALI
Zoneworks® XT Hive	CBULK-HVG	LBULK-HVG	
Dimensions (L x W x H)	346mm x 132mm x 86mm		
Directional Options	Available separately		

POWER, LAMPS AND BATTERY		CLP	L10
Power Consumption (Standby / Max)	0.4W / 4.7W		
Lamp(s)	LED Module 4000K / 30,000hrs		
Battery	Lithium Iron Phosphate	Lithium Nanophosphate®	
Voltage (V) / Milliamp per hour (mAh)	6.4V / 3200mAh	3.3V / 5000mAh	
Charging Method	Intelligent Current Limited Constant Voltage		
Rated Emergency Duration (Mins)	180		


TECHNICAL SPECIFICATIONS	
Operating Mode	Non-Maintained
Voltage (V) Frequency (Hz)	220-240V (50Hz)
Operating Temperature	0°C to 40°C
Viewing Distance (Exit Option)	20m
IP Rating (IP)	IP65
Impact Rating (IK)	IK08

LUMINAIRE CLASSIFICATION				
Without Automatic Testing	X	0	AD	180
With Automatic Testing	X	0	ADF	180

EXIT DECALS (AVAILABLE SEPARATELY)	
Up Arrow	BULKITE-DECAL-RU
Down Arrow	BULKITE-DECAL-RD
Left Arrow	BULKITE-DECAL-RL
Right Arrow	BULKITE-DECAL-RR


CEILING MOUNTING HEIGHT (M)	1 LUX SPACING TABLE AND MOUNTING HEIGHTS				0.5 LUX SPACING TABLE AND MOUNTING HEIGHTS			
	Escape Routes 1 Lux min. along centre line				Open (Anti-panic) Areas 0.5 Lux min. within core area Luminaires arranged in a regular array			
	Axial Spacing	Transverse Spacing	Axial to Wall	Transverse to Wall	Axial Spacing	Transverse Spacing	Axial to Wall	Transverse to Wall
2.7								
	11.7	11	5	4.7	12.5	10.2	3.9	4.2
3	12.1	11.4	5.1	4.8	13	10.7	4.1	4.5
4	13.3	12.7	5.4	5	14.7	12	5.3	5.7
5	14.1	12.7	5.6	5	16.1	12.9	4.6	4.9

PROTECTION	
Battery overvoltage & overcurrent protection	
Battery deep discharge protection	
Supply voltage polarity reversal protection	
Battery short-circuit protection (charging will resume upon removal of fault)	



Dimensions (mm)

OPTIONAL DECAL SET



*Warranty information located at: <https://clevertronics.co.uk/product-warranty-statement/>

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

clevertronics.co.uk

362 Stockley Close, West Drayton, London UB7 9BL
 Clevertronics International UK Ltd trading as Clevertronics, with registered number 11249539, whose registered office is at 843 Finchley Road London NW11 8NA. 248UK UK Catalogue 2021

