



LBULK-HVG

CLEVERTRONICS L10 BULKITE WEATHERPROOF EMERGENCY LIGHT



PRODUCT INFORMATION

Part Number	LBULK-HVG			
MIC	UKS01820030001			
Description	L10 Bulkite Weatherproof Emergency Light			
Construction	Base Material: Polycarbonate Diffuser Cover Material: Polycarbonate			
Mounting	Surface Mount			
Dimensions L x W x H	346mm x 132mm x 86mm			
Weight	1.2kg			
Operating Mode	Non-Maintained – Can be adjusted to Maintained via Jumper			
Testing System	Zoneworks XT HIVE (RF)			
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent current limited constant voltage			
Lamp(s)	LED module, L80/B20, 100,000hrs @ Ta 30c 6500K, Ra>80			
Diffuser	EXIT decals available separately			
Operating Voltage	220-240V AC; 50Hz			
Power Consumption	0.7Watts (Standby), 4.0Watts (Maintained Standby), 5.0Watts (Max)			
Total lumen output	395lm (Emergency) 395lm (Maintained)			
Rated Emergency Duration	180 minutes			
IP Rating	IP65			
IK Rating	IK08			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none">Battery overvoltage & overcurrent protectionBattery deep discharge protectionSupply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault)			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	BATTERY:L10 3.3V 5AH. 200mm lead, no Brkt
8050790	LED: HWSUB: CT10754-D2 Petrus LED Strip - 2835 LP/L10
8002964	DRIVER: PCA: CT10142-L9 6C150 CTP DALI HV ZW UK 250mA Batt
8003330	PCA: 2.4Ghz RF Node CT10748-A1 Int Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.